SALTO INVEST

Height [mm]	Width [mm]	Collector Spacing	Depth	Space between wall and power slots	Radiator Weight [kg]	Radiator capacity [dm3]	Power level [W] 75/65/20
902	550	500	141-151	46-56	7,5	4,1	501
902	650	600	141-151	46-56	8,0	4,5	578
1102	550	500	141-151	46-56	9,4	5,2	643
1102	650	600	141-151	46-56	10,5	5,7	721
1302	550	500	141-151	46-56	11,0	6,2	798
1302	650	600	141-151	46-56	12,4	6,8	890









SALTO INVEST

Radiator without secrets

The curved line of this radiator follows new trends in world design, taking care of unique finishing elements. The base of the construction is solid steel tubes with an exceptionally shiny surface. Products from the SALTO line perfectly suit the interiors in a minimalist and modern style.

- **Vertical pipes**: oval Ø 30 x 50
- **Horizontal pipes:** round Ø 20
- **Detail work:** radiator made from low-carbon steel with powder coated finish
- **Standard colours:** white RAL 9003 or anthracite RAL 7016
- **Mounting:** mounting kit included
- **Further information:** Heater assembly or electric heater available to order

KOLOR
RAL colour system and special colours available

6 YEARS
Warranty

95°C
Maximum temperature

10 bar
Maximum work pressure

Electric version available

Hydro-electric version available

Adittional hangers

Types of connections

Standard connections

Optional types of connections

Recommended valves kits details on pages 183-184

Axial valve

Straight valve

Angular valve

6+2 WARRANTY
2 additional years of warranty when purchasing valves